


LIFT MASTER BOOM, ORBIT TELESCOPING BOOM-LM-OBT-3-24

APPROX WEIGHT: 448.69 lbs.
DOES NOT INCLUDE WEIGHT OF POWER OR PACKAGING!!!

*** ANY ADDITIONS, DELETIONS, OR OMISSIONS MUST BE CORRECTED ON THIS DRAWING AS THIS DRAWING WILL BE CONSIDERED ALL INCLUSIVE ***

ALL GRAPHICS PROVIDED ARE FOR REFERENCE ONLY. IF CERTAIN DIMENSIONS ARE CRITICAL PLEASE VERIFY THOSE DIMENSIONS WITH YOUR SALESPERSON



*--MAXIMUM SINGLE HOOK CAPACITIES

DISTANCE	36"	48"	60"	72"	84"	96"	108"	120"	132"	144"
CAPACITY	3000	2750	2500	2250	2000	1750	1500	1250	1000	750

STANDARD FEATURES

MODEL NUMBER IS LM-OBT-3-24

CAPACITY IS 3,000 LBS

MAXIMUM TILT ANGLE IS 37°

OVERALL HEIGHT - 27 13/16"

HEIGHT (MAX TILTED) - 99 1/2"

LENGTH RETRACTED - 86 5/8"

LENGTH EXTENDED - 146 5/8"

OVERALL WIDTH IS 32"

36" MINIMUM HOOK POINT

144" MAXIMUM HOOK POINT

HOOK HEIGHT - 6"

HOOK HEIGHT (MAX TILTED) - 78 5/16"

USABLE FORK POCKET - 2 1/2"x7 1/2"

24" FORK POCKET CENTERS

FRAME DURABLE BAKED IN POWDER COATED BLUE FINISH

BOOM DURABLE BAKED IN POWDER COATED YELLOW FINISH

SPECIAL FEATURES

NONE

APPROX. WEIGHT / LOST LOAD = 448.69

MINIMUM EFFECTIVE THICKNESS = LESS THAN 1"

NEVER EXCEED LOAD CENTER

RATING PER FORKTRUCK

MANUFACTURERS GUIDELINES.

DO NOT USE THIS FORK TRUCK

ATTACHMENT IF LOAD WILL

EXCEED FORK TRUCK MANUFACTURER'S

LOAD CENTER RATING

DIMENSION TOLERANCE ± 1/4"

APPROVAL

I, THE UNDERSIGNED, AGREE THAT THE PRODUCT AS REPRESENTED SATISFIES DESIGN AND DIMENSION REQUIREMENTS. I ALSO ACKNOWLEDGE MY DUTY TO CONFIRM PRODUCT AND INSTALLATION COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL REGULATIONS AND STANDARDS.

UNITS REQUIRING APPROVAL DRAWINGS OR MODIFIED ARE NON-RETURNABLE

[] As drawn [] As marked

Signed: _____ Date: _____

Printed Name: _____

LEAD TIME WILL START UPON RECEIPT OF SIGNED APPROVAL DRAWING

DISTRIBUTOR'S NAME:

VESTIL MANUFACTURING

DRAWN BY: B.NOTHNAGEL

DATE: 7/1/2015

REFERENCE: X

SCALE: 1:22

QUOTED LEAD TIME: X

QUOTE # X

P.O.#

X

W.O.#

X

SALES:

X

FILE NAME:

08-007-140-001